

View Online at <https://aerobasegroup.com/nsn/4720-01-382-8918>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

1.480 inches

Minimum Inside Bending Radius:

12.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

16000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer spirally laid steel wire err-100

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

105.000 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0