

View Online at <https://aerobasegroup.com/nsn/4720-01-383-2269>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.810 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

14000.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer molded polyurethane err-100

Maximum Operating Pressure:

3500.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

7000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.000 inches

Special Features:

Inner conveying tube material-plastic, polyester

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0