

View Online at <https://aerobasegroup.com/nsn/4720-01-383-2362>

Cross Sectional Shape:

Round

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.560 inches 2nd end

Outside Diameter:

1.850 inches

Minimum Inside Bending Radius:

16.500 inches

Center To Center Distance Between Bolt Holes Along Width:

1.188 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.312 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.090 inches and 3.160 inches 2nd end

Flange Width:

3.060 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

Bolt Hole Diameter:

0.469 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

84.000 inches working

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon and air and water and hydraulic fluid, water base single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0