NSN 4720-01-383-4198

Inner conveying tube material-rubber, synthetic

Cross Sectional Shape:

Thread Direction:
Right-hand 1st end
Inside Diameter:

Tempurature Rating:

Outside Diameter:

1.000 inches

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-383-4198

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

1.480 inches
Minimum Inside Bending Radius:
12.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
16000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spirally laid steel wire err-100
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
1.000 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
65.000 inches
Special Features:

NSN 4720-01-383-4198

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0