Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-383-5303

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.780 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Black
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 2nd end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
30.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0