

View Online at <https://aerobasegroup.com/nsn/4720-01-383-5353>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.562 inches

Minimum Inside Bending Radius:

4.620 inches

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

8000.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer braided steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.0625 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.463 inches

Second End Swivel Action Capability:

Included

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0