## NSN 4720-01-383-5397

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-383-5397

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.704 inches
Minimum Inside Bending Radius:
9.000 inches
Angle Between Rigid Elbow Fittings In Deg:
180.0
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and nuts drilled for lockwire
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
2.000 inches 2nd end
Seat Angle:
12.0 degrees 1st end
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Fire resistant
Inside Surface Condition:

Smooth

## NSN 4720-01-383-5397

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length: 41.000 inches Special Features: Length does not include working length of fitting ae23204p-24 Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unj 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A542a0