

View Online at <https://aerobasegroup.com/nsn/4720-01-383-5565>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 2nd end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

**Outside Diameter:**

0.594 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Quick Disconnect Size:**

0.500 inches 2nd end

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

16 2nd end

**Burst Test Pressure:**

1000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

37.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

96.000 inches excluding end fittings

**Special Features:**

First end includes plug 1, p/n an806d6, cable 1 p/n 9m59-2-120p, sleeve 2, p/n 9m306-6; second end includes: union 1, p/n an815-8d, reducer 1, p/n an919-12d. Tee 1. P/n an938d8, valve 1, p/n ms28882-8, o-ring 4, p/n ms29512-08. Plug 1, p/n st7m378-8, sleeve 1, p/n 9m306-6, cable 1, p/n 9m59-2-120p; u/o f15e aircraft

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Unf 1st end

**Reference Number Differentiating Characteristics:**

As differentiated by special features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0