Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-384-8895

Cross Sectional Sha	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.406 inches	
Tempurature Rating:	
-65.0 degrees fahrenh	eit single response and 450.0 degrees fahrenheit single response
Outside Diameter:	
0.562 inches	
Minimum Inside Ben	ding Radius:
4.620 inches	
Connection Style:	
Swivel nut flare 2nd er	ıd
End Connection Des	ign:
Straight 1st end	
Connection Type:	
Threaded internal tube	a 1st end
Burst Test Pressure:	
8000.0 pounds per sq	uare inch
Layer Composition A	Ind Location:
Outer layer braided cc	rrosion resistant steel wire
Maximum Operating	Pressure:
1500.0 pounds per sq	uare inch
Thread Size:	
0.750 inches 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Flow Angle:	
45.0 degrees 2nd end	
Outer Covering Envi	ronmental Protection:
Acid resistant and alco	bhol resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant and solvent
resistant	
Inside Surface Cond	tion:
Smooth	
Measuring Method A	nd Length:
128.000 inches worki	
Thread Series Desig	
Unf 2nd end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0