## NSN 4720-01-384-9004



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-384-9004 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.298 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response **Outside Diameter:** 0.655 inches **Minimum Inside Bending Radius:** 2.500 inches **End Application:** Mcdonnell douglas c-17-aaircrft **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and 2nd layer braided polyester cord and outer layer braided textile yarn **Maximum Operating Pressure:** 4000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 8000.0 pounds per square inch

Smooth

Measuring Method And Length:
29.500 inches

Thread Series Designator:
Unjf 1st end

**Inside Surface Condition:** 

Shelf Life:

N/a

## NSN 4720-01-384-9004

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0