Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-385-7062

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.640 inches	
Minimum Inside Bending Radius:	
2.250 inches	
Connection Style:	
Swivel, plain 2nd end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external pipe 2nd end	
Burst Test Pressure:	
11000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided steel wire and outer layer molded polyurethane	
Maximum Operating Pressure:	
2750.0 pounds per square inch	
Thread Size:	
0.375 inches 1st end	
Hydrostatic Test Pressure:	
5500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
20.000 inches	
Thread Series Designator:	
Nptf 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-01-385-7062

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

