NSN 4720-01-385-9102

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-385-9102

Cross Sectional Shape
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.766 inches
Minimum Inside Bending Radius:
4.620 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end
Shelf Life:

N/a

NSN 4720-01-385-9102

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0