NSN 4720-01-386-1673

Cross Sectional Shape:

Thread Direction:
Right-hand 1st end
Inside Diameter:

Tempurature Rating:

Vacuum In Torr:

25.0

1.000 inches

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-386-1673

-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response
Outside Diameter:
1.490 inches
Minimum Inside Bending Radius:
6.000 inches
Exterior Color:
Black
End Application:
4920-01-272-5931
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded external tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
1000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer wrapped rubber, synthetic err-100
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
11.500 inches 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and abrasion resistant

NSN 4720-01-386-1673

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
60.000 inches
Second End Swivel Action Capability:
Included
Special Features:
Meets or exceeds sae 100r4 requirements, with braided fiber and spiral wire to prevent collapsing
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A542a0