NSN 4720-01-386-1792

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-386-1792

Cross Sectional Shape:
Cross Sectional Shape: Round
Thread Class:
3b 1st end Thread Directions
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer molded rubber, synthetic and 3rd layer braided steel wire and outer layer molded rubber,
synthetic
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
34.000 inches excluding end fittings
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Unjf 1st end

Thread Series Designator:

NSN 4720-01-386-1792

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0