## NSN 4720-01-386-3303

**Cross Sectional Shape:** 

Round

Thread Class: 2b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-386-3303

Inside Diameter:
0.188 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel, plain 2nd end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded external tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
Outer layer braided steel wire err-100
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.125 inches 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches
Second End Swivel Action Capability:
Included

## NSN 4720-01-386-3303

Nonmetallic Hose Assembly - Page 2 of 2



Meets or exceeds all requirements of sae 100r14

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0