## NSN 4720-01-386-3426

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-386-3426

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
2.500 inches
End Application:
6685-01-278-6114
Connection Style:
Swivel, plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1400.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
350.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
700.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches working
Special Features:

Elbow has a long drop

## NSN 4720-01-386-3426

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0