Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-386-3435

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.590 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
End Fitting Component And Material:	
Complete fitting steel all ends	
Connection Type:	
Threaded internal tube 1st end	
Second End Relationship With First End:	
Not identical	
Burst Test Pressure:	
20000.0 pounds per square inch	
First End Swivel Action Capability:	
Not included	
Layer Composition And Location:	
1st layer braided steel wire err-100	
Maximum Operating Pressure:	
5000.0 pounds per square inch	
Thread Size:	
0.250 inches 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
10000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
-	

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:

Smooth

Measuring Method And Length: 72.000 inches excluding end fittings

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0