Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-386-4313

| Cross Sectional Shape: |
|------------------------|
| Round                  |
| Thread Class:          |
| 3b 1st end             |
| Thread Direction:      |
| Right-hand 1st end     |

#### **Inside Diameter:**

0.500 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

## **Outside Diameter:**

0.970 inches

Minimum Inside Bending Radius:

#### 5.000 inches

**Exterior Color:** 

Blue

## **End Application:**

2350-01-305-0028

## **Connection Style:**

Swivel nut, gasket seal 1st end

## End Connection Design:

Straight 1st end

## End Fitting Component And Material:

Complete fitting steel all ends

#### **Connection Type:**

Threaded internal tube 1st end

## Second End Relationship With First End:

Identical

## Burst Test Pressure:

14000.0 pounds per square inch

#### First End Swivel Action Capability:

Included

## Layer Composition And Location:

1st layer braided wire err-100

## Maximum Operating Pressure:

3500.0 pounds per square inch

## Thread Size:

0.812 inches 1st end

# Hydrostatic Test Pressure:

7500.0 pounds per square inch

## Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

25.500 inches

# Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A542a0