NSN 4720-01-388-0638

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-388-0638 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.970 inches **Minimum Inside Bending Radius:** 7.000 inches **Exterior Color:** Blue **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 4250.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 8500.0 pounds per square inch **Outer Covering Environmental Protection:** Fire resistant **Inside Surface Condition:**

Measuring Method And Length:

32.000 inches

Smooth

NSN 4720-01-388-0638

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0