## NSN 4720-01-388-1245

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-388-1245

Inside Diameter:						
0.375 inches						
Tempurature Rating:						
-5.0 degrees fahrenheit single response and 120.0 degrees fahrenheit single response						
Outside Diameter:						
0.550 inches						
Minimum Inside Bending Radius:						
0.750 inches						
Connection Style:						
Swivel nut, flareless 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Electrostatic discharge capability and nuts drilled for lockwire						
Burst Test Pressure:						
900.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided polyamide cord						
Maximum Operating Pressure:						
300.0 pounds per square inch						
Thread Size:						
0.562 inches 1st end						
Seat Angle:						
12.0 degrees 1st end						
Hydrostatic Test Pressure:						
600.0 pounds per square inch						
Outer Covering Environmental Protection:						
Ozone resistant and salt water resistant and fuel resistant and mildew resistant						
Inside Surface Condition:						
Convoluted						
Measuring Method And Length:						
14.250 inches						
Special Features:						
Application jp-4						

## NSN 4720-01-388-1245

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0