Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-388-2789

Cross	Sectional Shape:
Round	1
Threa	d Direction:
Right-	hand 1st end
Inside	Diameter:
0.250	inches
Temp	urature Rating:
-40.0 (degrees fahrenheit and 212.0 degrees fahrenheit single response
Outsid	de Diameter:
0.590	inches
Minim	um Inside Bending Radius:
4.000	inches
Exteri	or Color:
Black	
End A	pplication:
2330-0	00-221-4939
Conne	ection Style:
Plain 1	1st end
End C	connection Design:
Straig	ht 1st end
Conne	ection Type:
Thread	ded external pipe 1st end
Burst	Test Pressure:
23200	.0 pounds per square inch
Layer	Composition And Location:
1st lay	ver braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maxin	num Operating Pressure:
5800.0) pounds per square inch
Threa	d Size:
0.250	inches 1st end
Hydro	static Test Pressure:
11600	.0 pounds per square inch
Outer	Covering Environmental Protection:
Abrasi	ion resistant
Inside	Surface Condition:
Smoot	th
Measu	uring Method And Length:
46.000) inches
Media	For Which Designed:
Fuel/o	il, hydrocarbon single response
Threa	d Series Designator:
Nintf 1	st end

NSN 4720-01-388-2789

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

