Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-388-4648

Cross Sectio	nal Shape:
Round	
Thread Class	:
3b 1st end	
Thread Direc	tion:
Right-hand 1s	t end
Inside Diame	ter:
0.188 inches	
Tempurature	Rating:
-55.0 degrees	fahrenheit and 300.0 degrees fahrenheit single response
Outside Dian	neter:
0.484 inches	
Minimum Ins	ide Bending Radius:
2.000 inches	
End Applicat	ion:
2350-01-081-8	3138
Connection S	Style:
Swivel nut flar	e 1st end
End Connect	ion Design:
Straight 1st er	nd
Connection 1	уре:
Threaded inte	rnal tube 1st end
Features Pro	vided:
Reusable end	fittings
Burst Test Pr	essure:
6000.0 pound	s per square inch
Layer Compo	sition And Location:
1st layer braid	ed textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabri
Maximum Op	erating Pressure:
1500.0 pound	s per square inch
Thread Size:	
0.438 inches	Ist end
Seat Angle:	
37.0 degrees	1st end
Hydrostatic 7	est Pressure:
3000.0 pound	s per square inch
Vacuum In To	prr:
50.8	
Inside Surfac	e Condition:
Smooth	
Measuring M	ethod And Length:
18.250 inches	



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0