NSN 4720-01-388-4662



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-388-4662 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.750 inches **Minimum Inside Bending Radius:** 1.750 inches **End Application:** Dry deck shelter **Connection Style:** Plain 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 2nd end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 900.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 225.0 pounds per square inch **Thread Size:** 0.375 inches 1st end **Hydrostatic Test Pressure:** 450.0 pounds per square inch **Inside Surface Condition:**

Hydrostatic Test Pressure: 450.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 24.000 inches Media For Which Designed: Air single response Thread Series Designator: Npt 1st end Shelf Life:

N/a

NSN 4720-01-388-4662

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0