Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-388-4662

	Cross Sectional Shape:
	Round
	Thread Direction:
	Right-hand 1st end
	Inside Diameter:
	0.375 inches
	Tempurature Rating:
	-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
	Outside Diameter:
	0.750 inches
	Minimum Inside Bending Radius:
	1.750 inches
	End Application:
	Dry deck shelter
	Connection Style:
	Plain 2nd end
	End Connection Design:
	Straight 2nd end
	Connection Type:
	Threaded external tube 2nd end
	Features Provided:
	Reusable end fittings
	Burst Test Pressure:
	900.0 pounds per square inch
	Layer Composition And Location:
	1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
	Maximum Operating Pressure:
	225.0 pounds per square inch
,	Thread Size:
	0.375 inches 1st end
	Hydrostatic Test Pressure:
,	450.0 pounds per square inch
	Inside Surface Condition:
	Smooth
	Measuring Method And Length:
	24.000 inches
	Media For Which Designed:
	Air single response
	Thread Series Designator:
	Npt 1st end
	Shelf Life:
	N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0