

View Online at <https://aerobasegroup.com/nsn/4720-01-388-4848>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.630 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

0.910 inches

Minimum Inside Bending Radius:

6.000 inches

End Application:

2350-01-081-8138

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

700.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and outer layer wrapped rubber, synthetic

Maximum Operating Pressure:

175.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

350.0 pounds per square inch

Vacuum In Torr:

10.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

45.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0