NSN 4720-01-388-4848

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-388-4848

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.630 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.910 inches
Minimum Inside Bending Radius:
6.000 inches
End Application:
2350-01-081-8138
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
700.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer wrapped rubber, synthetic
Maximum Operating Pressure:
175.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
350.0 pounds per square inch
Vacuum In Torr:
10.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
45.000 inches
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-388-4848

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0