

View Online at <https://aerobasegroup.com/nsn/4720-01-389-0346>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.650 inches

Minimum Inside Bending Radius:

2.500 inches

End Application:

1730-01-268-1631

Connection Style:

Swivel, plain 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external pipe 2nd end

Features Provided:

Nonskive

Burst Test Pressure:

10000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

2500.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Hydrostatic Test Pressure:

5000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.000 inches

Special Features:

Hose has a fire screen

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0