

View Online at <https://aerobasegroup.com/nsn/4720-01-389-2234>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-70.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Minimum Inside Bending Radius:

1.250 inches

Exterior Color:

Black

End Application:

6920-01-185-9279

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Perforated outer cover

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided fiber and 2nd layer braided fiber and outer layer molded polyurethane

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.437 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.500 inches

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiig:

A542a0