

View Online at <https://aerobasegroup.com/nsn/4720-01-389-2234>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-70.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.500 inches

**Minimum Inside Bending Radius:**

1.250 inches

**Exterior Color:**

Black

**End Application:**

6920-01-185-9279

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Perforated outer cover

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided fiber and 2nd layer braided fiber and outer layer molded polyurethane

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.437 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

15.500 inches

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiiig:**

A542a0