

View Online at <https://aerobasegroup.com/nsn/4720-01-389-2974>

Cross Sectional Shape:

Round

Inside Diameter:

1.781 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

2.094 inches

Minimum Inside Bending Radius:

12.500 inches

Angle Between Rigid Elbow Fittings In Deg:

90.0

Quick Disconnect Size:

2.000 inches 2nd end

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

3.000 inches 1st end

End Application:

U/o p15 fire truck

Flange Width:

3.000 inches 1st end

Connection Style:

Plain 1st end

Bolt Hole Diameter:

0.333 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Universal quick disconnect 2nd end

Burst Test Pressure:

300.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

100.0 pounds per square inch

Hydrostatic Test Pressure:

200.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.250 inches working

Flange Style:

Rectangular (includes square) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0