

View Online at <https://aerobasegroup.com/nsn/4720-01-389-7715>

Cross Sectional Shape:

Round

Inside Diameter:

1.020 inches

Temperature Rating:

-65.0 degrees fahrenheit and 145.0 degrees fahrenheit single response

Flange Thickness:

2.312 inches 1st end

Outside Diameter:

1.940 inches

Minimum Inside Bending Radius:

5.500 inches

Center To Center Distance Between Bolt Holes Along Width:

1.312 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.312 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

1.750 inches 1st end

End Application:

1560-01-106-9519

Flange Width:

1.750 inches 1st end

Connection Style:

Raised 1st end

Bolt Hole Diameter:

0.205 inches 1st end

Raised Face Height:

0.161 inches 1st end

Raised Face Diameter:

1.375 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Straight 1st end

Connection Type:

Unthreaded external hose 2nd end

Burst Test Pressure:

240.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and outer layer braided polyester cord

Maximum Operating Pressure:

120.0 pounds per square inch

Hydrostatic Test Pressure:

180.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.000 inches

Flange Style:

Rectangular (includes square) 1st end

Inside Diameter Hose Accommodated:

1.000 inches 2nd end

Special Features:

There is tee subassembly located off of the flanged end at 90.0 degrees with .7500-16 unjf-3b threads, made of aluminum

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0