

View Online at <https://aerobasegroup.com/nsn/4720-01-389-7805>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.770 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 125.0 degrees fahrenheit single response

**Outside Diameter:**

0.860 inches

**Minimum Inside Bending Radius:**

1.000 inches

**End Application:**

Alq184

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

14 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

750.0 pounds per square inch

**First End Swivel Action Capability:**

Included

**Layer Composition And Location:**

Outer layer braided polyamide cord err-100

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

400.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

9.800 inches working

**Special Features:**

Inner conveying tube material-plastic, polytetrafluoroethylene

**Thread Series Designator:**

Uns 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0