

View Online at <https://aerobasegroup.com/nsn/4720-01-389-9002>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-70.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.650 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

End Application:

Hyster corp. Forklift

Connection Style:

Flared 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 2nd end

Features Provided:

Perforated outer cover

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

1st layer braided fiber and 2nd layer braided fiber and outer layer polyester

Maximum Operating Pressure:

2250.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

121.100 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0