## NSN 4720-01-390-1034

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-390-1034 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** 180.0 degrees fahrenheit single response **Outside Diameter:** 1.156 inches **Minimum Inside Bending Radius:** 4.500 inches **Connection Style:** Plain 1st end **End Connection Design:** Straight 1st end **End Fitting Component And Material:** Complete fitting copper alloy all ends **Connection Type:** Threaded external tube 1st end **Second End Relationship With First End:** Identical **Burst Test Pressure:** 800.0 pounds per square inch First End Swivel Action Capability: Not included **Layer Composition And Location:** 1st layer spirally laid polyamide cord err-100 **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.750 inches 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 32.000 inches **Thread Series Designator:** Npt 1st end

Shelf Life:

N/a

## NSN 4720-01-390-1034

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0