NSN 4720-01-390-1072

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-390-1072

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.830 inches
Minimum Inside Bending Radius:
5.500 inches
End Application:
2350-01-081-8138
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
875.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and ozone resistant and mildew resistant and vibration resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
62.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and air and water single response

NSN 4720-01-390-1072

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator	:
Thread	Series	Designator	,

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0