NSN 4720-01-390-1075

Nonmetallic Hose Assembly - Page 1 of 2

Fuel/oil, hydrocarbon and air and water single response



View Online at https://aerobasegroup.com/nsn/4720-01-390-1075

Cross Sectional Shape:			
Round			
Thread Class:			
2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.880 inches			
Tempurature Rating:			
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response			
Outside Diameter:			
1.200 inches			
Minimum Inside Bending Radius:			
7.380 inches			
End Application:			
2350-01-081-8138			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
12 1st end			
Burst Test Pressure:			
1500.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric			
Maximum Operating Pressure:			
375.0 pounds per square inch			
Thread Size:			
1.312 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Outer Covering Environmental Protection:			
Fuel resistant and oil resistant and ozone resistant and mildew resistant and vibration resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
13.500 inches			
Media For Which Designed:			

NSN 4720-01-390-1075

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	ator:
--------	--------	--------	-------

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0