## NSN 4720-01-390-1075

Nonmetallic Hose Assembly - Page 1 of 2

Fuel/oil, hydrocarbon and air and water single response



View Online at https://aerobasegroup.com/nsn/4720-01-390-1075

Cross Sectional Shape:		
Round		
Thread Class:		
2b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.880 inches		
Tempurature Rating:		
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response		
Outside Diameter:		
1.200 inches		
Minimum Inside Bending Radius:		
7.380 inches		
End Application:		
2350-01-081-8138		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Thready Qty Per Inch (tpi):		
12 1st end		
Burst Test Pressure:		
1500.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric		
Maximum Operating Pressure:		
375.0 pounds per square inch		
Thread Size:		
1.312 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Outer Covering Environmental Protection:		
Fuel resistant and oil resistant and ozone resistant and mildew resistant and vibration resistant		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
13.500 inches		
Media For Which Designed:		

## NSN 4720-01-390-1075

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	-------------

Un 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0