Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-391-5857

GIU	oss Sectional Shape:
Rou	und
Ins	ide Diameter:
0.18	88 inches
Ter	npurature Rating:
-65	.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Out	tside Diameter:
0.3	12 inches
Min	nimum Inside Bending Radius:
2.0	00 inches
Со	nnection Style:
Pus	sh (internal) 2nd end
End	d Connection Design:
Stra	aight 2nd end
Со	nnection Type:
Inte	ernal quick disconnect 2nd end
Bui	rst Test Pressure:
120	000.0 pounds per square inch
Lay	ver Composition And Location:
Out	ter layer braided corrosion resistant steel wire
Ma	ximum Operating Pressure:
150	00.0 pounds per square inch
Нус	drostatic Test Pressure:
300	00.0 pounds per square inch
Flo	w Angle:
90.0	0 degrees 1st end
Ins	ide Surface Condition:
Sm	ooth
Mea	asuring Method And Length:
24.0	000 inches excluding end fittings
She	elf Life:
N/a	
Uni	it Of Measure:
Der	militarization:
No	
Fiig	3:
	42a0