Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-391-5860

Cross	Sectional Shape:
Round	
Thread	l Class:
3b 1st	end
Thread	Direction:
Right-h	and 1st end
Inside	Diameter:
0.406 i	nches
Tempu	irature Rating:
-65.0 d	egrees fahrenheit and 250.0 degrees fahrenheit single response
Outsid	e Diameter:
Betwee	en 0.743 inches and 0.789 inches
Minim	um Inside Bending Radius:
4.630 i	nches
Angle	Between Rigid Elbow Fittings In Deg:
0.0	
Conne	ction Style:
Swivel	nut flare 1st end
End C	onnection Design:
Elbow	1st end
Conne	ction Type:
Thread	led internal tube 1st end
Burst	Test Pressure:
8000.0	pounds per square inch
Layer	Composition And Location:
1st lay	er braided fiber and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated fabric
Maxim	um Operating Pressure:
2000.0	pounds per square inch
Thread	l Size:
0.750 i	nches 1st end
Seat A	ngle:
37.0 de	egrees 1st end
Hydro	static Test Pressure:
4000.0	pounds per square inch
Flow A	ingle:
90.0 de	egrees 1st end
Outer	Covering Environmental Protection:
Oil resi	stant and mildew resistant
Inside	Surface Condition:
Smoot	n
Measu	ring Method And Length:
21.500	inches

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0