## NSN 4720-01-391-8303

**Cross Sectional Shape:** 

25.000 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-391-8303

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.734 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Thready Qty Per Inch (tpi):
16 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
8000.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
Outer layer braided wire err-100
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.7188 inches 1st end
Seat Angle:
45.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:

## NSN 4720-01-391-8303

Nonmetallic Hose Assembly - Page 2 of 2



Inner conveying tube material-plastic, polytetrafluoroethylene

**Thread Series Designator:** 

Unj 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0