NSN 4720-01-392-0366

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-392-0366

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-30.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.531 inches
Minimum Inside Bending Radius:
6.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer spirally wrapped fabric and 2nd layer helix wire coil and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
41.500 inches
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-392-0366

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0