Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-392-2300

oss Sectional Shape:	
bund	
read Class:	
1st end	
read Direction:	
ght-hand 1st end	
side Diameter:	
250 inches	
mpurature Rating:	
0.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
itside Diameter:	
510 inches	
nimum Inside Bending Radius:	
250 inches	
onnection Style:	
vivel nut flare 1st end	
d Connection Design:	
raight 1st end	
onnection Type:	
readed internal tube 1st end	
atures Provided:	
rforated outer cover	
irst Test Pressure:	
000.0 pounds per square inch	
yer Composition And Location:	
t layer braided fiber and 2nd layer braided fiber and outer layer polyester	
aximum Operating Pressure:	
00.0 pounds per square inch	
read Size:	
138 inches 1st end	
at Angle:	
.0 degrees 1st end	
drostatic Test Pressure:	
00.0 pounds per square inch	
side Surface Condition:	
nooth	
easuring Method And Length:	
0.000 inches	
read Series Designator:	
If 1st end	
elf Life:	
a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0