Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-392-2459

C	Cross Sectional Shape:
F	Round
Т	hread Class:
3	b 1st end
Т	hread Direction:
F	Right-hand 1st end
h	nside Diameter:
C	.140 inches
T	empurature Rating:
-	65.0 degrees fahrenheit single response and 203.0 degrees fahrenheit single response
C	Dutside Diameter:
С	.360 inches
C	Connection Style:
S	Swivel nut flare 2nd end
E	nd Connection Design:
S	Straight 1st end
C	Connection Type:
Т	hreaded internal tube 1st end
Ν	laximum Operating Pressure:
5	0.0 pounds per square inch
T	hread Size:
С	.438 inches 1st end
S	Seat Angle:
3	7.0 degrees 2nd end
ŀ	lydrostatic Test Pressure:
1	25.0 pounds per square inch
F	low Angle:
g	0.0 degrees 2nd end
h	nside Surface Condition:
S	Smooth
Ν	leasuring Method And Length:
g	8.000 inches working
	hread Series Designator:
	Jnjf 1st end
	Shelf Life:
	I/a
ι	Init Of Measure:
-	
	Demilitarization:
٨	lo
F	iig:
A	1542a0