NSN 4720-01-392-3881

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-392-3881

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 257.0 degrees fahrenheit single response
Outside Diameter:
1.625 inches
Minimum Inside Bending Radius:
6.000 inches
End Application:
4940-01-025-9856
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer spirally laid steel wire and 3rd layer braided textile yarn and outer layer molded rubber,
synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.250 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
600.000 inches excluding end fittings
Media For Which Designed:
Fuel/oil, hydrocarbon and air and water single response
Thread Series Designator:
Npt 1st end
Shelf Life:

N/a

NSN 4720-01-392-3881

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0