NSN 4720-01-392-5368

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-392-5368

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 165.0 degrees fahrenheit single response
Outside Diameter:
0.600 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and outer layer molded rubber, synthetic
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
104.375 inches
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-01-392-5368

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0