## NSN 4720-01-392-6550

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-392-6550

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.250 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 165.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.480 inches  |
| Minimum Inside Bending Radius:  |
| 4.000 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 1250.0 pounds per square inch   |
| Layer Composition And Location:                                       |
| 1st layer braided fiber and outer layer molded rubber, synthetic      |
| Maximum Operating Pressure:   |
| 200.0 pounds per square inch  |
| Thread Size:  |
| 0.438 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 400.0 pounds per square inch  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 104.375 inches  |
| Thread Series Designator:   |
| Unf 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 4720-01-392-6550

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0