Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-393-4556

Cros	s Sectional Shape:
Roun	d
Threa	ad Class:
2b 1s	it end
Threa	ad Direction:
Right	-hand 1st end
Insid	e Diameter:
0.250) inches
Temp	ourature Rating:
-40.0	degrees fahrenheit and 212.0 degrees fahrenheit single response
Outs	ide Diameter:
0.530) inches
Minir	num Inside Bending Radius:
2.000) inches
End /	Application:
3930	-01-330-8906
Conr	nection Style:
Swive	el nut flare 2nd end
End	Connection Design:
Straig	ght 1st end
Conr	nection Type:
Threa	aded internal tube 1st end
Burs	t Test Pressure:
2300	0.0 pounds per square inch
Laye	r Composition And Location:
1st la	yer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic
Maxi	mum Operating Pressure:
5750	0 pounds per square inch
Threa	ad Size:
0.438	B inches 1st end
Seat	Angle:
37.0	degrees 2nd end
Flow	Angle:
	degrees 2nd end
Insid	e Surface Condition:
Smoo	
Meas	suring Method And Length:
29.12	20 inches
Medi	a For Which Designed:
Hydra	aulic fluid, water base single response
Threa	ad Series Designator:
Unf 2	nd end

NSN 4720-01-393-4556

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

