Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-393-4564

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.530 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
3930-01-330-8906
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
23000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
5750.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
67.500 inches
Media For Which Designed:
Hydraulic fluid, water base single response
Thread Series Designator:
Unf 2nd end

## NSN 4720-01-393-4564

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

