Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-393-5257

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
1.750 inches
End Application:
2330-01-378-9997
Connection Style:
Plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 2nd end
Features Provided:
Reusable end fittings
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and outer layer molded rubber, ethylene propylene
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.500 inches 2nd end
Hydrostatic Test Pressure:
450.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and age resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
64.000 inches
Thread Series Designator:
Nptf 2nd end
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0