Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-394-6219

| Cross Sectional Shape:  |  |
|---|--|
| Round   |  |
| Thread Class:   |  |
| 3b 1st end  |  |
| Thread Direction:   |  |
| Right-hand 1st end  |  |
| Inside Diameter:  |  |
| 0.375 inches  |  |
| Tempurature Rating:   |  |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |  |
| Outside Diameter:   |  |
| 0.620 inches  |  |
| Minimum Inside Bending Radius:  |  |
| 2.000 inches  |  |
| End Application:  |  |
| Wiggins lift co. Forklift   |  |
| Connection Style:   |  |
| Swivel nut flare 2nd end  |  |
| End Connection Design:  |  |
| Straight 1st end  |  |
| Connection Type:  |  |
| Threaded internal tube 1st end  |  |
| Burst Test Pressure:  |  |
| 10000.0 pounds per square inch  |  |
| Layer Composition And Location:                                       |  |
| 1st layer braided steel wire and outer layer molded rubber, synthetic |  |
| Maximum Operating Pressure:   |  |
| 3000.0 pounds per square inch   |  |
| Thread Size:  |  |
| 0.562 inches 2nd end  |  |
| Seat Angle:   |  |
| 37.0 degrees 2nd end  |  |
| Flow Angle:   |  |
| 90.0 degrees 2nd end  |  |
| Outer Covering Environmental Protection:                              |  |
| Oil resistant and weatherproof  |  |
| Inside Surface Condition:   |  |
| Smooth  |  |
| Measuring Method And Length:  |  |
| 23.500 inches working   |  |
| Thread Series Designator:   |  |
| Unf 2nd end   |  |
|   |  |

## NSN 4720-01-394-6219

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

